

**Precise non-contact
temperature measurement
from -50 °C to 1050 °C**



Features:

- One of the smallest infrared sensors worldwide with up to 22:1 optical resolution
- Rugged sensing head - usable up to 180 °C ambient temperature without cooling
- Two-piece design with easy accessible programming keys and LCD backlit display
- Built-in USB interface for simple sensor setup via mobile phone or PC
- Selectable analog outputs:
0/4 – 20 mA, 0 – 5 V, 0 – 10 V, thermocouple type K
- Optional EtherNet/IP, Profinet, Ethernet TCP / Modbus TCP, Modbus RTU, RS485, RS232 interface or relay outputs (2 x optically isolated)
- Easy and flexible exchange of sensing heads

General specifications

Environmental rating	IP 65 (NEMA-4)
Operating temperature range ¹⁾	-20 °C ... 180 °C (120 °C for LT 02) (sensing head) -20 °C ... 85 °C (electronics)
Storage temperature	-40 °C ... 180 °C (120 °C for LT 02) (sensing head) -40 °C ... 85 °C (electronics)
Operating air humidity range	10 – 95 %, non condensing
Vibration (sensor)	IEC 60068-2-6 (sinus shaped) IEC 60068-2-64 (broadband noise)
Shock (sensor)	IEC 60068-2-27 (25G and 50G)
Weight	40 g (sensing head) / 420 g (electronics)

Electrical Specifications

Output / analog (2x)	0 / 4 – 20 mA, 0 – 5 / 10 V, thermocouple K, alarm
Output / alarm	24 V / 50 mA (open collector)
Relay outputs (optional)	2 x 60 V DC / 42 V AC _{eff} ; 0.4 A; optically isolated
Outputs / digital	built-in USB-interface, Optional EtherNet/IP, Profinet, Ethernet TCP / Modbus TCP, Modbus RTU, RS485, RS232 interface or relay outputs (2 x optically isolated)
Output impedances	mA max. 500 Ω (with 8 – 36 V DC) mV min. 100 kΩ load impedance thermocouple 20 Ω
IO Pins (3x)	flexible programming as in- or output: external emissivity adjustment, ambient temperature compensation, uncommitted value, trigger (reset of holdfunctions), alarm output (open collector 24 V / 50 mA)
Cable length	1 m (standard), 3 m, 8 m, 15 m
Power	8 - 30 V DC 1.2W

Measurement specifications

Measuring Temperature range (scalable via programming keys or software)	-50 °C ... 650 °C (LT 02) -50 °C ... 800 °C (LT 15) -50 °C ... 1050 °C (LT 22)
Spectral range	8 – 14 μm
Optical resolution (90% energy)	22:1 15:1 2:1
Smallest spot size	0,6 mm @10 mm (LT22 + CF lens)
Measurement uncertainty ^{2), 3), 4), 5), 7)}	±1 % or ±1 °C
Repeatability ^{2), 3), 4), 5), 7)}	±0.1 % or ±0.1 °C
Temperature resolution (display)	0.1 K
NETD ^{4), 5), 6)}	60 mK (LT 02) 25 mK (LT 10) 35 mK (LT 22)
Response time	40 ms (LT02) 115 ms (LT10 & LT22)
Emissivity/ Setting (adjustable via programming keys or software)	0.05 – 1.100
Transmissivity/ Setting (adjustable via programming keys or software)	0.05 – 1.100
Signal processing (parameter adjustable via programming keys or software, respectively)	Peak hold, valley hold, average; extended hold function with threshold and hysteresis
Software / App	IR Mobile App / Optris CompactPlus Connect

1) The LCD displays capacity may be limited at ambient temperatures below 0 °C

2) Whichever is greater

3) $T_{obj} > 0 °C$

4) $\epsilon = 1$


5) Response time = 200ms

6) $T_{obj} = 25 °C$


7) at ambient temperature $23 \pm 5 °C$

Optical specifications


Optics CTi LT SF, D:S = 22:1



Optics CTi LT CF, D:S = 22:1 (far field = 1.5:1)



Optics CTi LT SF with additional CF lens (ACCTCF)/ far field = 1.5:1



More optical data: <https://optris.com/optris-calculator/>



Dimensions (in mm)

